



**Ceiling-Mount
18 to 36" Air
Circulator**

**Mobile Tilttable
Carriage Air
Circulator**

**Industrial Air
Circulators**

- Totally enclosed motors (open dripproof on 42" and 48" models)
- Ball bearing motors
- OSHA-compliant wire guards

Corrosion-resistant galvanized steel housing and steel propellers. Single-phase units include power cord with grounded molded plug. 3-phase units include 10-ft. pigtail prewired for 460V. Great for factories, warehouses, and agricultural applications. UL and C-UL Listed.

MOUNTING ACCESSORIES

Ceiling-Mount Kit—Quick-turn knobs allow easy tilt adjustment and multidirectional airflow. Hardware included.

Suspension-Mount Kit—For rafter or ceiling I-beam. Hardware and safety support cable included.

Wall-Mount Kit—Hardware and safety support cable included. Gray polyester powder-coated steel.

Dock Arm Kit—Includes light kit (lamp not included) and mounting arm. Yellow powder-coated galvanized steel.

Mobile Kit—Portable fixture for air circulator. Includes wheels, station feet, handles, and hardware.

Mobile Tilttable Carriage Kit—Stable portable carriage can be easily rolled about. Quick-turn knobs allow easy tilt adjustment and multidirectional airflow. Hardware included.

Blade Dia.	Phase	WITH CEILING-MOUNT KIT		WITH SUSPENSION-MOUNT KIT		WITH WALL-MOUNT KIT		WITH DOCK ARM KIT		WITH MOBILE KIT		WITH MOBILE TILTTABLE CARRIAGE KIT	
		Item No.	Each	Item No.	Each	Item No.	Each	Item No.	Each	Item No.	Each	Item No.	Each
Direct-Drive Circulators With Mounting Accessories													
18"	1	7AN94	426.50	7AN95	385.25	7J122	623.00	7J119	751.00	—	—	—	—
20"	1	7AN96	436.50	7AN97	395.25	7J123	633.50	7J120	761.00	—	—	—	—
24"	1	7AN98	468.25	7AN99	427.00	7J124	665.00	7J121	792.50	7AP00	426.25	7AP01	483.25
30"	1	7AP02	536.00	7AP03	477.25	7J125	732.50	—	—	7AP04	476.25	7AP05	542.00
36"	1	7AP06	564.50	7AP07	505.50	—	—	—	—	7AP08	505.00	7AP09	579.00
42"	1	7J777	737.50	7AP10	608.50	—	—	—	—	7AP11	612.50	7AP12	704.00
42"	3	7J781	921.00	7J787	792.00	—	—	—	—	7J789	795.50	7J791	887.50
48"	1	7J778	927.00	7AP13	798.00	—	—	—	—	7AP14	802.00	7AP15	933.50
48"	3	7J782	1,181.00	7J788	1,052.00	—	—	—	—	7J790	1,056.00	7J792	1,188.00
Belt-Drive Circulators With Mounting Accessories													
36"	1	7AP16	781.00	7AP17	722.50	—	—	—	—	7AP18	726.00	7AP19	846.50
42"	1	7J779	995.50	7AP20	866.50	—	—	—	—	7AP21	870.00	7AP22	961.50
42"	3	7J783	1,238.00	7J793	1,109.00	—	—	—	—	7J795	1,113.00	7J797	1,205.00
48"	1	7J780	1,082.00	7AP23	953.00	—	—	—	—	7AP24	957.00	7AP25	1,089.00
48"	3	7J784	1,331.00	7J794	1,202.00	—	—	—	—	7J798	1,205.00	7J798	1,337.00

Blade Dia.	CFM High	CFM Low	Air Vel. (fpm) @ 20 ft.	Air Vel. (fpm) @ 40 ft.	Air Vel. (fpm) @ 60 ft.	Fan RPM	Motor HP	Phase	Operating Amps	No. of Blades	Outside Dia.	Max. Depth	WITHOUT MOUNTING ACCESSORY	
													Item No.	Each
Direct-Drive Circulators Without Mounting Accessories														
18"	3600	2400	415/274	250/165	110/73	1075/750	1/4	1	1.7/1.6	3	19 1/2"	13 1/2"	4VAC9	295.50
20"	4500	3000	490/323	300/198	150/99	1075/750	1/4	1	1.7/1.6	3	21 1/2"	13 1/2"	4VAD1	305.50
24"	6100	4100	350/245	140/100	50/35	1075/750	1/2	1	3.7/3.4	3	25 1/2"	13 1/2"	4VAD2	337.25
30"	9600	7000	400/280	165/115	65/45	825/600	1/2	1	4.9/4.1	3	31 1/2"	13 1/2"	4VAD3	387.50
36"	12,500	9100	372/261	235/164	179/125	825/600	1/2	1	4.9/4.1	3	37 1/2"	13 1/2"	4VAD4	415.75
42"	16,000	11,600	418/262	284/204	240/173	825/600	3/4	1	8.9/6.1	3	43 1/2"	21 1/4"	4VAD5	519.00
42"	16,000	11,600	418	284	240	825	3/4	3	3.6-3.8/1.9	3	43 1/2"	21 1/4"	13F063	702.00
48"	19,500	14,100	464/279	344/260	316/232	825/600	3/4	1	8.9/6.1	3	50"	21 1/4"	4VAD6	708.50
48"	19,500	14,100	464	344	316	825	3/4	3	3.6-3.8/1.9	3	50"	21 1/4"	13F064	962.00
Belt-Drive Circulators Without Mounting Accessories														
36"	14,000	8400	417/292	263/184	200/140	460/304	1/2	1	4.9/4.1	6	37 1/2"	21 1/4"	4VAD7	632.50
42"	18,000	11,500	470/295	320/230	270/195	470/380	3/4	1	8.9/6.1	6	43 1/2"	21 1/4"	4VAD8	776.50
42"	18,000	11,500	470	320	270	470	3/4	3	3.2-3.4/1.7	6	43 1/2"	21 1/4"	13F065	1,020.00
48"	21,000	14,000	500/300	370/280	340/250	390/260	3/4	1	8.9/6.1	6	50"	21 1/4"	4VAD9	863.50
48"	21,000	14,000	500	370	340	390	3/4	3	3.2-3.4/1.7	6	50"	21 1/4"	13F066	1,112.00

Blade Dia.	CEILING-MOUNT KIT		SUSPENSION-MOUNT KIT		WALL-MOUNT KIT		DOCK ARM KIT		MOBILE KIT		MOBILE TILTTABLE CARRIAGE KIT	
	Item No.	Each	Item No.	Each	Item No.	Each	Item No.	Each	Item No.	Each	Item No.	Each
Mounting Accessories for Direct-Drive Circulators												
18"	—	—	—	—	—	—	—	—	—	—	—	—
20"	4VAE4	131.00	—	—	6RJVO	196.75	6XZJ3	324.25	—	—	—	—
24"	—	—	—	—	—	—	—	—	—	—	—	—
30"	—	—	4VAE6	89.70	—	—	—	—	4VAE8	88.85	4VAF1	145.95
36"	4VAE5	148.30	—	—	—	—	—	—	—	—	4VAF2	154.25
42"	—	—	—	—	—	—	—	—	—	—	4VAF3	163.25
48"	13F067	218.75	—	—	—	—	—	—	4VAE9	93.50	4VAF4	185.25
Mounting Accessories for Belt-Drive Circulators												
36"	4VAE5	148.30	—	—	—	—	—	—	—	—	4VAF6	213.75
42"	—	—	4VAE6	89.70	—	—	—	—	4VAE9	93.50	4VAF4	185.25
48"	13F067	218.75	—	—	—	—	—	—	—	—	4VAF5	225.25



No. 1LXN2



**Assembled
Ceiling-Mount
Air Circulators**

- Totally enclosed motors
- Ball bearings
- OSHA-compliant wire guards

Direct drive circulators tilt up or down 90° and swivel 360° to direct air for spot or general cooling. Heavy-gauge, welded construction. Suitable for operation in dirty and dusty environments. Precision steel propellers are carefully balanced to assure maximum air movement. Steel wire guard has black powder-coated finish. Units include a secondary safety support cable, ceiling-mount bracket, and 10-ft., 3-cond. power cord with grounded, molded plug.

Blade Dia.	CFM High	Air Vel. (fpm) @ 20 ft.	Voltage	Motor HP	Motor RPM	Operating Amps	No. of Blades	Item No.	\$ Each
36"	10,900	440	115V	1/2	825	6	3	1LXN2	1,239.00
48"	19,100	543	115V	1	850	9.1	3	1LXN3	1,951.00



No. 1LXN4



Assembled Outdoor High-Velocity Air Circulator

- Totally enclosed motor
- Ball bearings
- OSHA-compliant black powder-coated steel wire guards

Bell-shaped, heavy-duty, plastic rotomolded housing provides outstanding concentrated air velocity at distances of 100 ft. or more. Barrel can be tilted to direct airflow. Suitable for operation in dirty, dusty, and moist environments. Precision steel propellers are carefully balanced to assure maximum air movement. 10-ft., 3-cond. power cord with grounded, molded plug. Required mounting accessories (sold separately) make this fan great for numerous applications including golf courses, factories, dairy, horse, or poultry barns.

Blade Dia.	CFM High	Air Vel. (fpm) @ 20 ft.	Voltage	Motor HP	Motor RPM	Operating Amps	No. of Blades	Item No.	\$ Each
30"	10,600	970	115V	1	1140	10.6	3	1LXN4	2,151.00
Mounting Accessories									
Ceiling-Mounting Bracket For Use with No. 1LXN4; Includes Safety Cable								1LXN5	408.00
Tree-Mounting Bracket For Use with No. 1LXN4								1LXN6	367.50



No. 6ALD4

**SCHAEFER
Wall/Ceiling-Mounted
Air Circulators**

- Totally enclosed air-over motors
- Ball bearings
- Zinc-plated wire guards with white powder-coated finish (Nos. 6ALE2 and 6ALE3 are black)

Unique deep guard design produces greater air movement to reduce heat stress and improve air quality at significantly lower noise levels. 115V fans include 5-ft. cord with grounded plug.

WARNING: Guards are not OSHA-compliant. Fans should be mounted above 8 ft.

Blade Dia.	CFM High	Voltage	Phase	Motor HP	Motor RPM	Operating Amps	No. of Blades	Mfr. Model	Item No.	\$ Each
Wall (Mounting Hardware Included)										
8"	448	115V	1	1/100	1550	0.6	5	VK8	6ALD3	202.75
12"	1470	115V	1	1/10	1725	1.3	3	VK12	6ALD4	310.75
20"	5473	115V	1	1/2	1725	3.8	3	VK20	6ALD5	433.50
24"	7863	115V	1	1/2	1725	4.8	3	VK24	6ALD6	502.00
24"	7756	230V	3	1/2	1750	1.2	3	VK24-3	6ALD7	574.50
36"	11,400	115V	1	1/2	825	7	3	VK36	6ALD8	659.50
36"	11,384	230V	3	1/2	825	2.3	3	VK36-3	6ALD9	679.00
Ceiling (No Hardware Included)										
36"	11,693	115V	1	1/2	825	7	3	VKC36	6ALE0	672.00
36"	11,693	230V	3	1/2	825	2.3	3	VKC36-3	6ALE1	699.50
36"	11,693	115V	1	1/2	825	7	3	VKC36-B	6ALE2	672.00
36"	11,693	230V	3	1/2	825	2.3	3	VKC36-B-3	6ALE3	706.50