



Utility Exhaust Belt-Drive Blowers

For commercial kitchen exhaust or spark-resistant industrial applications. Scroll rotates in 45° increments to 8 positions; shipped in upblast position. Bolted access door and 1" threaded drain connection point on bottom of blower. Gray powder-coated heavy ga. steel housing. Weather hood included. Drive package components packed separately. UL and C-UL Listed.

- UL-762 Listed for Restaurant Exhaust Appliances (YZHW)
- Aluminum wheel & rub ring
- Max. inlet air temp.: 300°F
- Max. ambient: 104°F

Note: For external mount only.

For UL762 applications, scroll must remain in upblast position for proper grease draining.

Review OSHA Codes. OSHA complying guards required when fan blades are exposed and within reach of personnel.



WARNING: Use a hazardous location motor where flammable vapors are involved.

Wheel Dia. (in.)	CFM Air Delivery @ Static Pressure Shown*							Blower Motor		Sones @ 0.750" SP @ Max. BHP†	Dimensions (in.)												W/OUT DRIVE PACKAGE**			
	0.250"	0.500"	1.000"	1.500"	2.000"	2.500"	3.000"	RPM	HP		A	B	C	E	F	G	H	J	K	M	N	Item No.	\$ Each			
											COMPLETE WITH DRIVE PACKAGE**												Item No.	\$		
8 1/2	836	771	696	518				2048	1/4	13.0	0.25	7HT06	1,407.00			7HT07	1,517.00								5ZPJ7	1,102.00

* Performance certified is for installation type B: free inlet, ducted outlet. † Power rating (BHP) does not include transmission losses. Performance ratings do not include the effects of appurtenances (accessories). The AMCA Certified ratings Seal applies to air performance ratings only. ‡ Motor is rated 208-230V. ** Drive package consists of appropriate motor, belt, and sheaves to obtain the performance listed.