


## Wall Mount Cabinet Supply Fan



Designed for commercial and industrial applications requiring assembled packaged units able to deliver high volumes of air at low static pressures. Fans are completely assembled and ready for installation. Construction includes galvanized steel fan panel, fabricated propeller and bolted cabinets. Fan includes wall mounting angles for easy installation.


- Supply damper is bottom-pivoting spring return
- Air handling quality bearings meet minimum of L10-100,000 hours
- Maximum inlet air temperature: 104° F
- Variable pitch adjustable motor pulley to optimize fan performance



UL/cUL 705




CSA Certified Motor



A	B
28 1/4 in	34 1/8 in

## Performance Characteristics



## Construction Features

Impeller Diameter (Typ.)	24 in
Impeller Type	Propeller
Impeller Material	Fabricated Steel
Max Inlet Temp	104 °F
Bearing Type	Sealed Pillow Block
Drive Package Description	Drives Assembled
Warranty Length	1 Year

## Motor Information

Motor Item Number	50M238
Voltage	115/208-230
Hertz (Cycle)	60 Hz
Motor Phase	1
Motor Enclosure	Totally Enclosed Air-Over
RPM	1,725 rpm
Full Load Amps	8.0/4.0-4.0

## Other Components

Component	Description	Item #
Fan Description	Supply Fan	—
Driver Sheave	1VL44x5/8	3X276
Driven Sheave	BK95H	3X600
Driven Bushing	H x 3/4	3X573

## Air & Sound Performance

Motor HP	Max BHP	Fan RPM	CFM @	0.000" SP	0.125" SP	0.250" SP	0.375" SP
1/2	0.58	778	CFM	4988	4206	3321	1962
			Sones	15.1	13.6	12.3	11.7

Performance certified is for installation type A: Free inlet, Free outlet. Power rating (BHP) does not include transmission losses. Performance ratings include the effects of a birdscreen and damper in the air stream. Speed (RPM) shown is nominal. Performance is based on actual speed of test. The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values are for installation type A: Free inlet hemispherical sone levels.

Catalog 405, January 2010

## Operating Range of Drive Package

Turns Open	FRPM @ 0 TO	FRPM @ 1/2 TO	FRPM @ 1 TO	FRPM @ 1 1/2 TO	FRPM @ 2 TO	FRPM @ 2 1/2 TO	FRPM @ 3 TO	FRPM @ 3 1/2 TO	FRPM @ 4 TO	FRPM @ 4 1/2 TO	FRPM @ 5 TO
Approx. FRPM	778	756	737	717	697	678	658	638	619	599	579