

## Variable Speed Electronically Commutated (EC) Ventilator



Designed to meet the general clean air exhaust requirements for industrial and commercial buildings. Features a fully rolled windband bead for increased stability and easy transport. Fresh outside air is drawn in under the motor cover to maximize motor life. Energy Saving units feature EC motors which allow up to 80% useable turndown. Motor features potentiometer dial for speed adjustment. Optional Variable-Speed Control Kit (43Y140) can be used to remotely control speed.

- Aluminum backward inclined, nonoverloading centrifugal wheel design
- Maximum inlet air temperature: 130° F
- NEMA 1 junction box located in motor enclosure
- Optional NEMA 1 and 4 disconnects available
- High-efficiency brushless DC motor
- UL/cUL 705 Listed for Power Ventilators



## GREEN Product

- Variable Speed capable of 80% turn down at a minimum of 85% efficiency at all speeds
- Meets Minimum & Optimize Energy Performance

## AMCA Sound &amp; Air




Dayton Electric Mfg. Co. certifies that the ventilators shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.

## UL/cUL 705




E53236



A	B	C	D
17 in	21 3/4 in	14 5/8 in	4 in

## Performance Characteristics



## Construction Features

Impeller Diameter (Typ.)	8 1/4 in
Impeller Type	Backward Inclined Centrifugal
Impeller Material	Aluminum
Max Inlet Temp	130 °F
Warranty Length	1 Year

## Motor Information

Motor Item Number	43Y135
Voltage	115
Hertz (Cycle)	60 Hz
Motor Phase	1
Motor Enclosure	Totally Enclosed
RPM	rpm
Full Load Amps	3.1

## Air &amp; Sound Performance

Motor HP	Max BHP	Fan RPM	CFM @	0.000" SP	0.125" SP	0.250" SP	0.375" SP	0.500" SP	0.625" SP	0.750" SP
1/6	0.01	860	CFM	326	208	—	—	—	—	—
			Sones	2.1	2.2	—	—	—	—	—
1/6	0.03	1140	CFM	432	349	247	—	—	—	—
			Sones	4.4	4.3	4.5	—	—	—	—
1/6	0.09	1725	CFM	654	602	544	486	419	340	222
			Sones	9.5	9.4	9.3	9.3	9.4	9.4	10.2

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings include the effects of a birdscreen in the airstream. The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet fan sone levels.