Job Name: Mark: Submitted By: Date:11/4/2025

Variable Speed Electronically Commutated (EC) Ventilator



Designed to meet the general clean air exhaust requirements for industrial and commercial buildings. Features a fully rolled windband bead for increased stability and easy transport. Fresh outside air is drawn in under the motor cover to maximize motor life. Energy Saving units feature EC motors which allow up to 80% useable turndown. Motor features potentiometer dial for speed adjustment. Optional Variable-Speed Control Kit (43Y140) can be used to remotely control speed.

- Aluminum backward inclined, nonoverloading centrifugal wheel design
- Maximum inlet air temperature: 130° F
- NEMA 1 junction box located in motor enclosure
- Optional NEMA 1 and 4 disconnects available
- High-efficiency brushless DC motor
- UL/cUL 705 Listed for Power Ventilators




GREEN Product

- Variable Speed capable of 80% turn down at a minimum of 85% efficiency at all speeds
- Meets Minimum & Optimize Energy Performance




Dayton Electric Mfg. Co. certifies that the ventilators shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.





Performance Characteristics



Construction Features

Impeller Diameter (Typ.)	18 1/2 in				
Impeller Type	Backward Inclined Centrifugal				
Impeller Material	Aluminum				
Max Inlet Temp	130 °F				
Warranty Length	1 Year				

Motor Information

Motor Item Number	43Y139				
Voltage	115				
Hertz (Cycle)	60 Hz				
Motor Phase	1				
Motor Enclosure	Open				
RPM	rpm				
Full Load Amps	12.4				

Air & Sound Performance

Motor HP	Max BHP	Fan RPM	CFM @	0.000" SP	0.125" SP	0.250" SP	0.375" SP	0.500" SP	0.625" SP	0.750" SP	0.875" SP
1	0.26	730	CFM	2839	2668	2469	2213	1882	_	_	_
· ·	0.20	730	Sones	7.4	8.7	7.2	7.4	6.7	_	_	_
1	0.35	0.35 810	CFM	3150	2997	2832	2624	2375	2053	_	_
·	0.55		Sones	8.8	9.9	8.7	8.4	8.2	7.5	_	_
1	0.48	900	CFM	3500	3364	3219	3052	2858	2624	2347	1821
			Sones	11.3	11.7	10.9	10.2	10.1	9.7	9.2	8.4

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings include the effects of a birdscreen in the airstream. The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet fan sone levels.