Dayton

Stock No. 4HZ46

Job Name:
Mark:

Submitted By:
Date:11/29/2026

Power Roof Ventilators

Centrifugal Direct-Drive Upblast Wall-Mount Exhaust Ventilator



Designed for use in restaurants, schools, commercial, and industrial applications to exhaust contaminated air from kitchen range hoods, up and away from the building. Leakproof, spun aluminum construction features a fully rolled windband for increased stability.

- Aluminum backward inclined, nonoverloading centrifugal wheel design
- NEMA 1 junction box located in motor enclosure
- Optional NEMA 1 and 4 disconnects available
- Maximum inlet air temperature: 300º F
- UL/cUL 705 Listed for Power Ventilators
- UL/cUL 762 Listed for Restaurant Exhaust Appliances


AMCA Sound & Air

Dayton Electric Mfg. Co. certifies that the ventilators shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program.

UL/cUL 762


E53236
MH12596

CSA Certified Motor



A	B	C	D	E	F
19 3/4 in	24 7/8 in	23 3/4 in	17 3/8 in	16 7/8 in	12 1/2 in

Performance Characteristics



Construction Features

Impeller Diameter (Typ.)	13 1/4 in
Impeller Type	Backward Inclined Centrifugal
Impeller Material	Aluminum
Max Inlet Temp	300 °F
Warranty Length	1 Year

Motor Information

Motor Item Number	4YU19
Voltage	115
Hertz (Cycle)	60 Hz
Motor Phase	1
Motor Enclosure	Vented
RPM	860 rpm
Full Load Amps	2

Air & Sound Performance

Motor HP	Max BHP	Fan RPM	CFM @	0.000" SP	0.125" SP	0.250" SP	0.375" SP
1/8	0.07	860	CFM	1180	1057	914	675
			Sones	8.5	8.3	7.7	6.9

Performance certified is for installation type A: Free inlet, Free outlet. Performance ratings do not include the effects of appurtenances (accessories). The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a hemispherical free field calculated per AMCA Standard 301. Values shown are for installation type A: Free inlet hemispherical sone levels.