

## In-Line Cabinet Ventilator




High performance exhaust ventilators designed for residential, commercial, institutional and industrial applications. Factory assembled for horizontal discharge but can be rotated to vertical discharge in the field. Constructed of galvanized steel with a removable access panel on the bottom of unit. Hardware and mounting brackets are included.

- Single-speed motors feature thermal overload protection
- Electrical access cover on housing exterior allows easy external wiring
- Spring loaded aluminum backdraft damper eliminates rattling
- Exhaust outlets are field rotatable from horizontal to vertical discharge
- Acoustic insulation absorbs sound for quiet operation

AMCA Air  
 Dayton Electric Mfg. Co. certifies that the ventilators shown herein are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.

UL/cUL 507  
 E19455

CSA Certified Motor



<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>F</b>
14 in	11 7/8 in	11 1/4 in	8 in	8 in	12 7/8 in
<b>G</b>					
10 in					

## Performance Characteristics

No Fan Curve Available.

## Construction Features

<b>Impeller Type</b>	Backward Inclined Centrifugal
<b>Impeller Material</b>	Polypropylene
<b>Max Inlet Temp</b>	104 °F
<b>Warranty Length</b>	1 Year

## Motor Information

<b>Motor Item Number</b>	21EC10
<b>Voltage</b>	115
<b>Hertz (Cycle)</b>	60 Hz
<b>Motor Phase</b>	1
<b>Motor Enclosure</b>	Open Drip Proof
<b>RPM</b>	900 rpm
<b>Full Load Amps</b>	0.45

## Air & Sound Performance

Motor HP	Max BHP	Fan RPM	CFM @	0.000" SP	0.125" SP	0.250" SP	0.375" SP	0.500" SP	0.625" SP	0.750" SP
—	—	900	Sones	254	226	203	178	145	109	70
				0.6	0.5	0.9	1.0	1.3	1.5	1.5

Performance certified is for installation type D: Ducted inlet, Ducted outlet. Performance ratings include the effects of a backdraft damper. Speed (RPM) shown is nominal. Performance is based on actual speed of test. The sound ratings shown are loudness values in fan sones at 5 ft. (1.5 m) in a spherical free field calculated per AMCA Standard 301. Values shown are for installation type D: Ducted inlet spherical sone levels. Ratings do not include the effects of duct end correction. Ratings are based on 10 Ft. of insulated duct. The AMCA Certified Ratings Seal applies to air performance only.